



Bally Alpha 2 PRO Wave IDeck 300cd/M² Capacitive Touch 60Hz-75Hz

Basic Information

• Place of Origin: China

Brand Name: Anwell Touch
 Certification: CE,RoHS,FCC
 Model Number: AW150CB-GB02

Minimum Order Quantity: 2 Pieces Price: Negotiable

Packaging Details: Standard carton boxDelivery Time: 8-15 working days

Payment Terms: TT

Supply Ability: 1000 pieces per Month



Product Specification

Brightness: 300cd/m²
Response: 5 Msec
Viewing Angle: 178/178(°)

Touch Technology: Capacitive Touch
 Touch Cover: Glass T=1.8mm

• Touch Construction: G+G

• Interface: USB-B Female

Input Source: FingerPower Consumption: 25W

• Operating Temperature: $-10 \sim +65(^{\circ}\text{C})$ • Humidity Range (RH): $0^{\circ}\text{C} \sim 45^{\circ}\text{C}$

• Active Area: 373.8mmx71.6mm

Highlight: bally alpha 2 pro wave ideck,

bally gaming touch ideck button,

capacitive touch gaming touch ideck button



More Images



Product Description

Bally Alpha 2 PRO Wave iDeck

The same size as the prototype, dedicated to upgrade and replace the touch button panel on the Bally Alpha 2 pro Wave model

Net Weight	1.62kg
Gross Weight	2.5 kg
Product Dimension	465mm x 160mm x 39mm

Specifications Bally Alpha 2 PRO Wave iDeck		
Resolution	1920x1080	
Colors	Silver	
Number of Touches	Single-touch (multitouch optional)	
Brightness	300cd/m ²	
Response	5 msec	
Viewing Angle	178/178(°)	
Contrast Ratio	1000:1	
Backlight Lifetime (hours)	LED / 50,000h	
Touch Technology	P-CAP	
Touch Connector	USB	
Touch Life (Contacts)	Unlimited	
Surface Hardness	7H	
Output	DC12V	
Frenquency	60Hz-75Hz	
Power consumption	25W	
Operating Temperature	Operating:0°C~45°C	
operating remperature	Storage:-20°C-55°C	
Humidity Range (RH)	Operating:10%-80%RH, 40"C Storage:10%-80%RH, 40°C	
Housing material	Metal	





Shenzhen Anwell Touch Technology Co., Ltd.





15989592597@163.com (2) anwelltouch.com



301, Building A, No. 51, Youganyuan Road, Anliang Community, Yuanshan Street, Shenzhen