



22 Inch 1680*1050 Aristocrat Gaming PCAP Touch Screen Monitor With VGA/DVI/USB

Our Product Introduction

for more products please visit us on anwelltouch.com


Basic Information

- Place of Origin: China
- Brand Name: Anwell Touch
- Certification: CE, RoHS, FCC
- Model Number: AW220CB-G801
- Minimum Order Quantity: 2 Pieces
- Price: Negotiable
- Packaging Details: Standard carton box
- Delivery Time: 15 working days
- Payment Terms: TT
- Supply Ability: 5000 pieces per Month





Product Specification

- Aspect Ratio: 16:9
- Resolution: 1680*1050
- Interface Type: DVI, Usb, VGA
- Response Time: 5ms
- Contrast Ratio: 1000:1
- Brightness: 350cd/m2
- Colors: 16.7M
- Viewing Angle: 85/85/80/80 (Typ.)(CR≥10)
- Touch Technology: 10 Points Multi-Touch Capacitive Touch Screen
- Warranty: 12 Months
- Highlight: aristocrat gaming pcap touch screen, 1680*1050 gaming pcap touch screen, 1680*1050 pcap touch screen monitor



More Images



Product Description

22 Inch 1680*1050 Aristocrat Gaming PCAP Touch Screen Monitor With VGA/DVI/USB

Product Description



22inch Capacitive touch screen game monitor

Touch Gaming monitor Feature:

- Compatible with 3M/ELOs protocol
- Touch signal input : USB
- Signal input: VGA/DVI
- Support embedded rack mounted / VESA wall mounted
- AU,EU,US,UK plug available
- Application: Game machine,Interactive kiosk, Interactive digital signage,Industrial enclosure, Cabinet, In-wall devices

Specifications

22 Inch Capacitive Touch Monitor Data	
Model	AW220CS-G801
Monitor Color	Silver
Resolution	1680 x 1050
Colors	16.7 million
Number of Touches	Single-touch (multitouch optional)
Brightness	300cd/m ²
Response	5 msec
Viewing Angle	178/178(°)
Contrast Ratio	1000:1
Backlight Lifetime (hours)	LED / 50,000h
Touch Technology	Capacitive touch
Touch Connector	USB

Touch Panel Drivers	compatible with 3M/ELO protocol
Touch Life (Contacts)	Unlimited
Surface Hardness	7H
Power Supply	Input AC110 ~ 240V
Output	DC12V
Frequency	60Hz-75Hz
Power consumption	25W
Operating Temperature	-10 ~ +65(°C)
Humidity Range (RH)	10%-90%
Housing material	Metal or Aluminum



