



## 350cd/M2 55inch Curved Touch Screen Monitor 3M/ELO Protocol For Cabinets

### Our Product Introduction

for more products please visit us on [anwelltouch.com](http://anwelltouch.com)

#### Basic Information

- Place of Origin: China
- Brand Name: Anwell Touch
- Certification: CE,Rohs,FCC
- Model Number: AW550CB-G901
- Minimum Order Quantity: 2 Pieces
- Price: Negotiable
- Packaging Details: Standard carton box
- Delivery Time: 8-15 working days
- Payment Terms: TT
- Supply Ability: 1000 pieces per Month




#### Product Specification

- Product Name: 55 Inch Curved Game PCAP Touch Monitor
- Viewing Angle: 85/85/85/85 (Typ.)(CR≥10)
- Contrast Ratio: 1000:1
- Response Time: 5ms
- Colors: 16.7M
- Brightness: 350cd/m2
- Touch Technology: Capacitive Touch Screen
- Power Supply: Input AC110 ~ 240V/50 ~ 60Hz
- Warranty: 12 Months
- Compatible With: 3M/ELO Microtouch Protocol
- Aspect Ratio: 16:9
- Series: For Gaming
- Highlight: 55inch curved touch screen monitor,  
curved touch screen monitor 3m/elo,  
55inch curved touch screen computer monitor



#### More Images



## Product Description

Compatible With 3M/ELO Protocol 55inch Curved Touch Screen Gaming Monitor For Cabinets

### Product Description



#### 55inch Capacitive touch Curved screen game monitor

##### Touch Gaming monitor Feature:

- Compatible with 3M/ELOs protocol
- Touch signal input : RS232 / USB
- Signal input: VGA/DVI/HD-MI
- Support embedded rack mounted / VESA wall mounted
- AU,EU,US,UK plug available
- Application: Game machine,Interactive kiosk, Interactive digital signage,Industrial enclosure, Cabinet, In-wall devices

Specifications	
55 Inch Capacitive Touch <b>Curved screen</b> Monitor Data	
Model	AW550CB-G901
Monitor Color	Black
Resolution	3840 x 2160
Colors	16.7 million
Number of Touches	Single-touch ( multitouch optional)
Brightness	300cd/m <sup>2</sup>
Response	5 msec
Viewing Angle	178/178(°)
Contrast Ratio	1000:1
Backlight Lifetime (hours)	LED / 50,000h
Touch Technology	Capacitive touch
Touch Connector	USB/RS232
Touch Panel Drivers	compatible with 3M/ELO protocol

Touch Life (Contacts)	Unlimited
Surface Hardness	7H
Power Supply	Input AC110 ~ 240V
Frenquency	60Hz-75Hz
Power consumption	25W
Operating Temperature	-10 ~ +65(°C)
Humidity Range (RH)	10%-90%
Housing material	Metal or Aluminum
Mounting	75mm and 100mm VESA mount; Rear mount ; Flush mount with included brackets





"C" type



**Shenzhen Anwell Touch Technology Co., Ltd.**



+8615989592597



15989592597@163.com



anwelltouch.com

301, Building A, No. 51, Youganyuan Road, Anliang Community, Yuanshan Street, Shenzhen