



# Single Touch Or Multitouch 49 Inch Capacitive C Curved Monitor Touchscreen Gaming Monitor Acrylic Style

#### **Basic Information**

Place of Origin: China

Brand Name: Anwell Touch
 Certification: CE,Rohs,FCC
 Model Number: AW490CB-G902

Minimum Order Quantity: 2 PiecesPrice: Negotiable

Packaging Details: Standard carton boxDelivery Time: 8-15 working days

Payment Terms: TT

• Supply Ability: 1000 pieces per Month



#### **Product Specification**

Product Name:
 49 Inch Curved Game PCAP Touch Monitor

• Interface Type: D-SUB, Usb, HD-MI

• Viewing Angle: 85/85/85 (Typ.)(CR≥10)

Contrast Ratio: 1000:1
Response Time: 5ms
Colors: 16.7M
Brightness: 350cd/m2

Touch Technology: Capacitive Touch Screen
 Power Supply: Input AC110 ~ 240V/50 ~ 60Hz

• Warranty: 12 Months

Compatible With: 3M/ELO Microtouch Protocol

• Aspect Ratio: 16:9

Series: For Gaming

Highlight: multitouch curved monitor touchscreen,

multitouch curved touchscreen display,



#### More Images





#### **Product Description**

Single Touch Or Multitouch 49 Inch Capacitive C Curved Monitor Touchscreen Gaming Monitor Acrylic Style

#### **Product Description**



## 49inch Capacitive touch Curved screen game monitor

#### **Touch Gaming monitor Feature:**

- Compatible with 3M/ELOs protocol
- Touch signal input : RS232 / USB
- Signal input: VGA/DVI/HD-MI
- Support embedded rack mounted /

VESA wall mounted

- · AU,EU,US,UK plug available
- Application: Game machine,Interactive kiosk, Interactive digital signage,Industrial enclosure, Cabinet, In-wall devices

#### **Specifications** 49 Inch Capacitive Touch Curved screen Monitor Data Model AW490CB-G902 Monitor Color Black Resolution 1920 x 1080 Colors 16.7 million Number of Touches Single-touch (multitouch optional) Brightness 300cd/m<sup>2</sup> Response 5 msec 178/178(°) Viewing Angle Contrast Ratio 1000:1 Backlight Lifetime (hours) LED / 50,000h Touch Technology Capacitive touch USB/RS232 **Touch Connector Touch Panel Drivers** compatible with 3M/ELO protocol

Touch Life (Contacts)	Unlimited
Surface Hardness	7H
Power Supply	Input AC110 ~ 240V
Frenquency	60Hz-75Hz
Power consumption	25W
Operating Temperature	-10 ~ +65(°C)
Humidity Range (RH)	10%-90%
Housing material	Metal or Aluminum
Mounting	75mm and 100mm VESA mount; Rear mount ; Flush mount with included brackets







### **Shenzhen Anwell Touch Technology Co., Ltd.**

+8615989592597



301, Building A, No. 51, Youganyuan Road, Anliang Community, Yuanshan Street, Shenzhen