



21.5Inch Led Light Multi Touch Capacitive Touchscreen With USB RS232 Compatible With 3M For Game Machine

Our Product Introduction

for more products please visit us on anwelltouch.com

Basic Information

- Place of Origin: China
- Brand Name: Anwell Touch
- Certification: CE,RoHS,FCC
- Model Number: AW215CB-G804
- Minimum Order Quantity: 2 Pieces
- Price: Negotiable
- Packaging Details: Standard carton box
- Delivery Time: 15 working days
- Payment Terms: TT
- Supply Ability: 5000 pieces per Month



Product Specification

- Aspect Ratio: 16:9
- Resolution: 1920 X 1080
- Response Time: 5ms
- Contrast Ratio: 1000:1
- Brightness: 300cd/m2
- Type: Capacitive Touch
- Colors: 16.7M
- Viewing Angle: 85/85/80/80 (Typ.)(CR≥10)
- Touch Technology: 10 Points Multi-Touch Capacitive Touch Screen
- Warranty: 12 Months
- Highlight: 21.5inch multi capacitive touch screen,
21.5inch multi touch capacitive touchscreen,
usb multi capacitive touch screen



More Images



Product Description

21.5Inch Led Light Multi Capacitive Touch Screen Monitor With USB RS232 Compatible With 3M For Game Machine

Product Description



21.5 inch Capacitive touch screen game monitor

Touch Gaming monitor Feature:

- Compatible with 3M/ELOs protocol
- Touch signal input : RS232 / USB
- Signal input: VGA/DVI/HD-MI
- Support embedded rack mounted / VESA wall mounted
- AU,EU,US,UK plug available
- Application: Game machine,Interactive kiosk, Interactive digital signage,Industrial enclosure, Cabinet, In-wall devices

Specifications	
21.5 Inch Capacitive Touch Monitor Data	
Model	AW215CB-G804
Monitor Color	Black
Resolution	1920 x 1080
Colors	16.7 million
Number of Touches	Single-touch (multitouch optional)
Brightness	300cd/m ²
Response	5 msec
Viewing Angle	178/178(°)
Contrast Ratio	1000:1
Backlight Lifetime (hours)	LED / 50,000h
Touch Technology	Capacitive touch
Touch Connector	USB/RS232
Touch Panel Drivers	compatible with 3M/ELO protocol

Touch Life (Contacts)	Unlimited
Surface Hardness	7H
Power Supply	Input AC110 ~ 240V
Output	DC12V
Frenquency	60Hz-75Hz
Power consumption	25W
Operating Temperature	-10 ~ +65(°C)
Humidity Range (RH)	10%-90%
Housing material	Metal or Aluminum
Mounting	75mm and 100mm VESA mount; Rear mount ; Flush mount with included brackets





Shenzhen Anwell Touch Technology Co., Ltd.



+8615989592597



15989592597@163.com



anwelltouch.com

301, Building A, No. 51, Youganyuan Road, Anliang Community, Yuanshan Street, Shenzhen