



## LED Light Gaming Pcap Touch Screen 43 Inch 4K LED Bar Firelink Original Vertical Display

Our Product Introduction

for more products please visit us on [anwelltouch.com](http://anwelltouch.com)

### Basic Information

- Place of Origin: China
- Brand Name: Anwell Touch
- Certification: CE,Rohs,FCC
- Model Number: AW430CB-G841
- Minimum Order Quantity: 2 Pieces
- Price: Negotiable
- Packaging Details: Standard carton box
- Delivery Time: 15 working days
- Payment Terms: TT
- Supply Ability: 5000 pieces per Month



### Product Specification

- Size: 43 Inches
- Aspect Ratio: 16:9
- Resolution: 3840 X 2160
- Interface Type: DVI, DP, Usb,HD
- Response Time: 5ms
- Contrast Ratio: 1000:1
- Brightness: 300cd/m2
- Type: Capacitive Touch
- Colors: 16.7M
- Viewing Angle: 85/85/80/80 (Typ.)(CR≥10)
- Touch Technology: 10 Points Multi-Touch Capacitive Touch Screen
- Warranty: 1 Year
- Highlight: gaming pcap touch screen 43 inch ,  
pcap gaming touch screen ,  
4k gaming touch screen



### More Images



## Product Description

LED Light PCAP Touch Screen Game Touch Monitor 43 Inch 4K LED Bar Firelink Original Vertical Display

## Product Description



### 43 inch 4K Capacitive touch screen game monitor

#### Touch Gaming monitor Feature:

- Compatible with 3M/ELOs protocol
- Touch signal input : RS232 / USB
- Signal input: VGA/DVI/HD-MI
- Support embedded rack mounted / VESA wall mounted
- AU,EU,US,UK plug available
- Application: Game machine,Interactive kiosk, Interactive digital signage,Industrial enclosure, Cabinet, In-wall devices

| Specifications                           |                                     |
|--|-------------------------------------|
| 43 Inch 4K Capacitive Touch Monitor Data |                                     |
| Model                                    | AW430CB-G841                        |
| Monitor Color                            | Black                               |
| Resolution                               | 3840 x 2160                         |
| Colors                                   | 16.7 million                        |
| Number of Touches                        | Single-touch ( multitouch optional) |
| Brightness                               | 400cd/m <sup>2</sup>                |
| Response                                 | 5 msec                              |
| Viewing Angle                            | 178/178(°)                          |
| Contrast Ratio                           | 1000:1                              |
| Backlight Lifetime (hours)               | LED / 50,000h                       |
| Touch Technology                         | Capacitive touch                    |
| Touch Connector                          | USB/RS232                           |
| Touch Panel Drivers                      | compatible with 3M/ELO protocol     |

|                       |   |
|-----------------------|---|
| Touch Life (Contacts) | Unlimited   |
| Surface Hardness      | 7H  |
|                       |   |
| Power Supply          | AC110 ~ 240V  |
| Frenquency            | 60Hz-75Hz   |
| Power consumption     | 25W   |
|                       |   |
| Operating Temperature | -10 ~ +65(°C)   |
| Humidity Range (RH)   | 10%-90%   |
| Housing material      | Metal or Aluminum   |
| Mounting              | 75mm and 100mm VESA mount; Rear mount ;<br>Flush mount with included brackets |



