



Single Touch Or Multitouch 49 Inch Capacitive C Curved Monitor Touchscreen Gaming Monitor Acrylic Style

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Anwell Touch
- Certification: CE,Rohs,FCC
- Model Number: AW490CB-G902
- Minimum Order Quantity: 2 Pieces
- Price: Negotiable
- Packaging Details: Standard carton box
- Delivery Time: 8-15 working days
- Payment Terms: TT
- Supply Ability: 1000 pieces per Month



Product Specification

- Product Name: 49 Inch Curved Game PCAP Touch Monitor
- Interface Type: D-SUB, Usb, HD-MI
- Viewing Angle: 85/85/85/85 (Typ.)(CR≥10)
- Contrast Ratio: 1000:1
- Response Time: 5ms
- Colors: 16.7M
- Brightness: 350cd/m2
- Touch Technology: Capacitive Touch Screen
- Power Supply: Input AC110 ~ 240V/50 ~ 60Hz
- Warranty: 12 Months
- Compatible With: 3M/ELO Microtouch Protocol
- Aspect Ratio: 16:9
- Series: For Gaming
- Highlight: **49 inch capacitive touchscreen gaming monitor , C curved multitouch gaming screen ,**

for more products please visit us on anwelltouch.com

Product Description

Single Touch Or Multitouch 49 Inch Capacitive C Curved Monitor Touchscreen Gaming Monitor Acrylic Style

Product Description



49inch Capacitive touch Curved screen game monitor

Touch Gaming monitor Feature:

- Compatible with 3M/ELOs protocol
- Touch signal input : RS232 / USB
- Signal input: VGA/DVI/HD-MI
- Support embedded rack mounted / VESA wall mounted
- AU,EU,US,UK plug available
- Application: Game machine,Interactive kiosk, Interactive digital signage,Industrial enclosure, Cabinet, In-wall devices

Specifications	
49 Inch Capacitive Touch Curved screen Monitor Data	
Model	AW490CB-G902
Monitor Color	Black
Resolution	1920 x 1080
Colors	16.7 million
Number of Touches	Single-touch (multitouch optional)
Brightness	300cd/m ²
Response	5 msec
Viewing Angle	178/178(°)
Contrast Ratio	1000:1
Backlight Lifetime (hours)	LED / 50,000h
Touch Technology	Capacitive touch
Touch Connector	USB/RS232
Touch Panel Drivers	compatible with 3M/ELO protocol

Touch Life (Contacts)	Unlimited
Surface Hardness	7H
Power Supply	Input AC110 ~ 240V
Frenquency	60Hz-75Hz
Power consumption	25W
Operating Temperature	-10 ~ +65(°C)
Humidity Range (RH)	10%-90%
Housing material	Metal or Aluminum
Mounting	75mm and 100mm VESA mount; Rear mount ; Flush mount with included brackets







Shenzhen Anwell Touch Technology Co., Ltd.



+8618420495337



jasssiieee@gmail.com



anwelltouch.com

301, Building A, No. 51, Youganyuan Road, Anliang Community, Yuanshan Street, Shenzhen